



PZTA92/93

PNP SILICON TRANSISTOR


HIGH VOLTAGE TRANSISTOR

DESCRIPTION

The UTC **PZTA92/93** are high voltage PNP transistors, designed for telephone signal switching and for high voltage amplifier.

FEATURES

- * Collector-emitter voltage: $V_{CE0}=-300V$ (UTC PZTA92)
 $V_{CE0}=-200V$ (UTC PZTA93)
- * Complement to UTC PZTA42/43
- * Collector power dissipation: $P_{C(MAX)}=1W$



ORDERING INFORMATION

Ordering Number	Package	Pin Assignment			Packing
		1	2	3	
PZTA92G-AA3-R	SOT-223	B	C	E	Tape Reel
PZTA93G-AA3-R	SOT-223	B	C	E	Tape Reel

<p>PZTA92G-AA3-R</p> <p>(1) Packing Type (2) Package Type (3) Green Package</p>	<p>(1) R: Tape Reel (2) AA3: SOT-223 (3) G: Halogen Free and Lead Free</p>
---	--

MARKING

PZTA92	PZTA93
<p>PZTA92G □□□□ → Data Code 1</p>	<p>PZTA93G □□□□ → Data Code 1</p>

■ ABSOLUTE MAXIMUM RATING ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	PZTA92	-300	V
	PZTA93	-200	V
Collector-Emitter Voltage	PZTA92	-300	V
	PZTA93	-200	V
Emitter-Base Voltage	V_{EBO}	-5	V
Collector Current	I_C	-500	mA
Collector Power Dissipation	P_C	1	W
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$






Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C=-100\mu\text{A}, I_E=0$	PZTA92	-300		V
			PZTA93	-200		V
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C=-1\text{mA}, I_B=0$	PZTA92	-300		V
			PZTA93	-200		V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E=-100\mu\text{A}, I_C=0$	-5			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=-200\text{V}, I_E=0$	PZTA92		-0.25	μA
		$V_{CB}=-160\text{V}, I_E=0$	PZTA93		-0.25	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=-3\text{V}, I_C=0$			-0.10	μA
DC Current Gain (Note)	h_{FE}	$V_{CE}=-10\text{V}, I_C=-1\text{mA}$	60			
		$V_{CE}=-10\text{V}, I_C=-10\text{mA}$	80			
		$V_{CE}=-10\text{V}, I_C=-30\text{mA}$	80			
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=-20\text{mA}, I_B=-2\text{mA}$			-0.5	V
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C=-20\text{mA}, I_B=-2\text{mA}$			-0.90	V
Current Gain Bandwidth Product	f_T	$V_{CE}=-20\text{V}, I_C=-10\text{mA}, f=100\text{MHz}$	50			MHz
Collector Base Capacitance	C_{CB}	$V_{CB}=-20\text{V}, I_E=0, f=1\text{MHz}$	PZTA92		6	pF
			PZTA93		8	pF

Note: Pulse test: $P_W < 300\mu\text{s}$, Duty Cycle $< 2\%$, $V_{CE(SAT)} < 200\text{mV}$ (Class SIN)

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.