


SR220 THRU SR2200

SCHOTTKY BARRIER RECTIFIER

Reverse Voltage - 20 to 200 Volts Forward Current - 2.0 Ampere

DO-15



Dimensions in inches and (millimeters)

FEATURES

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ Metal silicon junction, majority carrier conduction
- ◆ Low power loss, high efficiency
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed:
250°C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

MECHANICAL DATA

Case: JEDEC DO-15 molded plastic body
Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity: Color band denotes cathode end
Mounting Position: Any
Weight: 0.014 ounce, 0.40 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
 Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.


| MDD Catalog Number | SYMBOLS | SR 220 | SR 230 | SR 240 | SR 250 | SR 260 | SR 270 | SR 280 | SR 290 | SR 2A0 | SR 2150 | SR 2200 | UNITS |
|---|-----------------|-------------|--------|--------|--------|--------|-------------|--------|--------|--------|---------|---------|-------|
| Maximum repetitive peak reverse voltage | V_{RRM} | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 150 | 200 | VOLTS |
| Maximum RMS voltage | V_{RMS} | 14 | 21 | 28 | 35 | 42 | 49 | 56 | 63 | 70 | 105 | 140 | VOLTS |
| Maximum DC blocking voltage | V_{DC} | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 100 | 200 | VOLTS |
| Maximum average forward rectified current 0.375" (9.5mm) lead length (see fig.1) | I_{AV} | 2.0 | | | | | | | | | | | Amp |
| Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) | I_{FSM} | 60.0 | | | | | | | | | | | Amps |
| Maximum instantaneous forward voltage at 2.0A | V_F | 0.55 | | 0.70 | | | 0.85 | | | 0.95 | | Volts | |
| Maximum DC reverse current at rated DC blocking voltage $T_A=25^\circ\text{C}$ $T_A=100^\circ\text{C}$ | I_R | 0.5 | | | | | | 0.2 | | 2.0 | | | mA |
| Typical junction capacitance (NOTE 1) | C_J | 220 | | | 80 | | | | | | | | pF |
| Typical thermal resistance (NOTE 2) | $R_{\theta JA}$ | 50.0 | | | | | | | | | | | °C/W |
| Operating junction temperature range | T_J | -65 to +125 | | | | | -65 to +150 | | | | | | °C |
| Storage temperature range | T_{STG} | -65 to +150 | | | | | | | | | | | °C |

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.


2. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted

RATINGS AND CHARACTERISTIC CURVES SR220 THRU SR2200


AVERAGE FORWARD RECTIFIED CURRENT, AMPERES




PEAK FORWARD SURGE CURRENT, AMPERES




INSTANTANEOUS FORWARD CURRENT, AMPERES



INSTANTANEOUS REVERSE CURRENT, MILLIAMPERES



JUNCTION CAPACITANCE, pF



TRANSIENT THERMAL IMPEDANCE, °C/W

