



NOTES:

- Housing: Thermoplastics, UL94V-0
- Contact: Copper Alloy
- Shell: Copper Alloy/Steel
- Voltage Current Rating: 1.5 AMP. 30V AC
- Insulation Resistance: 1000MΩ Min.
- Contact Resistance: 30 MΩ Max.
- Dielectric Withstanding Voltage: 500W AC
- Temperature Range: -35°C to +85°C
- Insulator color: Black/White
- Plastic material: PBT/LCP/Others
- Shell finish: Nickel plated/Tin-Lead plated
- Mechanical:
- Mating Force: 3.5KG MAX
- Umating Force: 0.7 KG MIN.
- Contact finish:
- 01: Selective Gold Flash
- 02: Selective Gold 3U”
- 03: Selective Gold 5U”
- 04: Selective Gold 15U”
- 05: Selective Gold 30U”

备注：侧弹分为外弹与内弹

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE	
X	±0.15
.X	±0.10
.XX	±0.05
.XXX	±0.03

单位	MM	制图	Z-Y-B	产品料号
UNITS		DRAWING		PRODUCT PART NO.
比例	1:1	审核		产品名称
SCALE		CHD		USB-AF无边沉板
日期	2009/10/20	核准		角法
DATE		APPD		版本
				VER
				A0

目錄

变更内容
MODIFICATION

日期
DATE