



RECOMMENDED PCB

目錄 MAPX	變更內容 MODIFICATION	日期 DATE
------------	----------------------	------------

规格: Specifications:
 电 器: Electrical:
 接触电阻: Contact Resistance
 50 milliohms MAX
 耐电压: Dielectric Withstanding Voltage:
 100 V AC AT Sea Level
 绝缘电阻: Insulation Resistance:
 100 MEGA ohms MIN

材料: Material:
 塑胶: Housing: Ulting Temperature Thermoplastics,
 UL 94V-0 耐高温塑胶
 端子: Contact: Copper Alloy 铜合金
 外壳: Shell: Copper Alloy 铜合金
 电镀: Finish:
 外壳: Shell: Nickel/Plating 镀镍
 端子: Contact: Plated gold in Mating Area;
 Tin On Solder Tails
 接触点镀金, 脚镀锡

Ordering Informating
 X - 5 - XX
 Contact plating
 01-Gold Flash
 02-5u" Gold/ Tin
 03-15u" Gold/ Tin
 04-30u" Gold/ Tin
 Plastic Color
 A=Black
 尺寸未注公差参考 ± 0.10

产品图
PRODUCT CHART DWG

公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	
X	±0.25	X'	±5'	审核 CHECK		产品名称 PRODUCT NAME	MINI 5P 母头 SMT
X	±0.20	X'	±2'	核准 APPD		角法 VIEW	
.XX	±0.15	.XX'	±1'	日期 DATE	2009/10/20	版本 VER	A0
.XXX	±0.10	.XXX'	±0.5'				