



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 10mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer LCP, UL94V-0  
PIN Brass Tin-plated  
Solder tads Brass Tin-plated

编号	尺寸 (mm)			
	A	B	C	D
A2501WF-02A	2.50	7.50	10.00	8.20
A2501WF-03A	5.00	10.00	12.50	10.70
A2501WF-04A	7.50	12.50	15.00	13.20
A2501WF-05A	10.00	15.00	17.50	15.70
A2501WF-06A	12.50	17.50	20.00	18.20
A2501WF-07A	15.00	20.00	22.50	20.70
A2501WF-08A	17.50	22.50	25.00	23.20
A2501WF-09A	20.00	25.00	27.50	25.70
A2501WF-10A	22.50	27.50	30.00	28.20
A2501WF-11A	25.00	30.00	32.50	30.70
A2501WF-12A	27.50	32.50	35.00	33.20
A2501WF-15A	35.00	40.00	42.50	40.70

制图  
DRAWN

变更内容  
DESCRIPTION

日期  
DATE

GENERAL TOLERANCE

制图

料号  
PART NO.

版本  
REV.

X.±0.25

X.±2°

品名  
TITLE

页次  
SHEET

.X±0.20

X.±1°

客户料号  
CUST. NO.

1/1

.XX±0.15

.XX±0.5°

审核

1/1

.XXX±0.10

.XXX±0.5°

单位  
UNITS

比例  
SCALE

MM

1:1